



# MT411

- Classic SKS stepped traction pattern combined with self cleaning steps
- Wear and cut resistant compounds
- Wide tread for optimum stability and lifetime
- Reinforced sidewall for enhanced protection.
- Optimal lug to void ratio provides maximum grip
- Conforms to the latest standards of ETRTO (European Tyre and Rim Technical Organization) and the TRA (Tire and Rim Association)



Size	Type	PR	Rim	Tread Depth	Overall Diameter	Section Width	Inflation Pressure	Loading Capacity	Speed (Km/h)				
23x8.50-12	T/L	6	7.00	mm	13	574	213	kPa	340	Kg	820	Km/h	10
				in.		22,60	8,39	psi	49	lbs	1805	mph	6
27.8.50-15	T/L	8	7.00	mm	13	678	215	kPa	350	Kg	1030	Km/h	10
				in.		26,69	8,46	psi	51	lbs	2270	mph	6
10-16.5	T/L	10	8.25	mm	19	779	261	kPa	520	Kg	2170	Km/h	10
				in.		30,67	10,28	psi	75	lbs	4780	mph	6
12-16.5	T/L	12	9.75	mm	19	830	312	kPa	550	Kg	2900	Km/h	10
				in.		32,68	12,28	psi	80	lbs	6385	mph	6
14-17.5	T/L	14	10.50	mm	19	992	351	kPa	550	Kg	3875	Km/h	10
				in.		39,06	13,82	psi	80	lbs	8538	mph	6
15-19.5	T/L	14	11.75	mm	21	1029	391	kPa	485	Kg	4565	Km/h	10
				in.		40,51	15,39	psi	70	lbs	10050	mph	6