



MT432

- Classic directional R4 tread design
- Wear and cut resistant compounds
- Reinforced side wall for enhanced protection
- Optimal lug to void ratio for enhanced traction, lifetime and protection
- Conforms to the latest standards of ETRTO (European Tyre and Rim Technical Organization) and the TRA (Tire and Rim Association)



Size	Type	PR	Rim	Tread Depth	Overall Diameter	Section Width	Inflation Pressure	Loading Capacity	Speed (Km/h)				
16.9-24	T/L	12	15.00	mm	27	1236	429	kPa	260	Kg	3250	Km/h	40
				in.		48,66	16,89	psi	38	lbs	7160	mph	25
16.9-28	T/L	12	15.00	mm	27	1435	430	kPa	260	Kg	3450	Km/h	40
				in.		56,50	16,93	psi	38	lbs	7600	mph	25
17.5L-24	T/L	10	15.00	mm	26	1241	445	kPa	190	Kg	1900	Km/h	40
				in.		48,86	17,52	psi	28	lbs	4180	mph	25
19.5L-24	T/L	12	17.00	mm	27	1314	495	kPa	230	Kg	3455	Km/h	40
				in.		51,73	19,49	psi	33	lbs	7610	mph	25
18.4-26	T/L	12	16.00	mm	27	1450	467	kPa	230	Kg	2985	Km/h	40
				in.		57,09	18,39	psi	33	lbs	6570	mph	25
21L-24	T/L	14	18.00	mm	29	1402	533	kPa	250	Kg	3075	Km/h	40
				in.		55,20	20,98	psi	36	lbs	6770	mph	25