

# MT511

- Classic directional industrial tread design
- Suitable for drive and steer use
- Wear and cut resistant compounds
- Reinforced side wall for enhanced protection
- Optimal lug to void ratio for enhanced traction, lifetime and protection
- Conforms to the latest standards of ETRTO (European Tyre and Rim Technical Organization) and the TRA (Tire and Rim Association)



INDUSTRIAL

Size	Type	PR	Rim		Overall Diameter	Section Width		Inflation Pressure		Loading Capacity
5.00-8	T/T	10	3.50D	mm	470	137	kPa	900	Kg	1295
				in.	18,50	5,39	psi	130	lbs	2850
6.00-9	T/T	10	4.00E	mm	540	160	kPa	850	Kg	1795
				in.	21,26	6,30	psi	123	lbs	3950
6.50-10	T/T	10	5.00F	mm	590	175	kPa	775	Kg	1965
				in.	23,23	6,89	psi	112	lbs	4330
7.00-12	T/T	14	5.00S	mm	683	192	kPa	1000	Kg	2670
				in.	26,89	7,56	psi	145	lbs	5880
7.00-15	T/T	14	5.50F	mm	750	200	kPa	945	Kg	3100
				in.	29,53	7,87	psi	137	lbs	6830
7.50-15	T/T	14	6.00G	mm	808	215	kPa	925	Kg	3375
				in.	31,81	8,46	psi	134	lbs	7430
8.25-15	T/T	14	6.50	mm	847	236	kPa	830	Kg	3830
				in.	33,35	9,29	psi	120	lbs	8430
18x7-8	T/T	14	4.33R	mm	465	173	kPa	900	Kg	1840
				in.	18,31	6,81	psi	130	lbs	4050
21x8-9	T/T	14	6.00E	mm	535	200	kPa	900	Kg	2300
				in.	21,06	7,87	psi	130	lbs	5060
23x10-12	T/T	12	8.00	mm	632	200	kPa	700	Kg	3290
				in.	24,88	7,87	psi	102	lbs	7240
23x9-10	T/T	16	7.00	mm	584	229	kPa	800	Kg	2300
				in.	22,99	9,02	psi	116	lbs	5060
250-15	T/T	16	7.50	mm	735	250	kPa	850	Kg	4350
				in.	28,94	9,84	psi	123	lbs	9580
27x10-12	T/T	14	8.00G	mm	690	250	kPa	750	Kg	3620
				in.	27,17	9,84	psi	110	lbs	7970
28x9-15 (8.15-15)	T/T	14	7.00	mm	710	220	kPa	800	Kg	3285
				in.	27,95	8,66	psi	116	lbs	7230
300-15	T/T	20	8.00	mm	840	300	kPa	900	Kg	6825
				in.	33,07	11,81	psi	130	lbs	15030